US ARMY FOREIGN SCIENCE AND TECHNOLOGY CENTER




ACCURACY IN DETERMINING THE HIGHT OF A RADIOSONDE

BY USING A TELEMETRIC ATTACHMENT TO -MALAKHIT- RADIOTHEODOLITE

AT AEROLOGICAL STATIONS OF THE HYDROMETEOROLOGICAL SERVICE

by

S. A. Budarina




Country: USSR

This document is a rendition of the original foreign text without any analytical or editorial comment.

Distribution of this document is unlimited. It may be released to the Clearinghouse, Department of Commerce, for sale to the general public.

NATIONAL TECHNICAL INFORMATION SERVICE Springfield, Va. 22151

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

TECHNICAL TRANSLATION

PSTC-HT-23-255-70

ENGLISH TITLE: ACCURACY IN DETERMINING THE HIGHT OF A RADIOSONDE

BY USING A TELEMETRIC ATTACHMENT TO -MALAKHIT-RADIOTHEODOLITE AT AEROLOGICAL STATIONS OF THE HYDROMETEOROLOGICAL SERVICE OF THE UZBEK SSR

FOREIGN TITLE: O TOCHNOSTT OPREDELENIYA VYSOTY RADIOZONDA DAL'NOMERNOY

PRISTAVKOY RADIOTEDDOLITA "MALAKHIT" NA AEROLOGICHESKIKH

STANTSIYAKH UCMS UZSSR

AUTHOR: S. A. Budarina

SOURCE: TASKENT SREDNEAZIATSKIY NAUCHNG-

ISSLEDOVATEL' SKIY

GIDROMETEOROLOGICHSKIY INSTITUT TRUDY NO 31 (46) TEMPERATURNYY REZHIM I ANALIZ FRONTOV GORAKH

pp. 156-169, 1967

Russian

Translated for FSTC by ACSI

NOTICE

The contents of this publication have been translated as presented in the original text. No attempt has been made to verify the accuracy of any statement contained herein. This translation is published with a minimum of copy editing and graphics preparation in order to expedite the dissemination of information. Requests for additional copies of this document should be addressed to the Defense Documentation Center, Cameron Station, Alexandria, Virginia, ATTN: TSR-1.

Cited below are the results of an altitude comparison based on a reading of a radiosonde pressure
unit, and calculated by measuring the slant range with
a range-finding attachment to a "Malachite" radio theodolite. The relationship between the altitude divergence and the balloon coordinates, the sheltered location of the horizontal site and the characteristics of
the subjacent media has been established. The results
of special base-line observations were used to calculate the systematic and mean square errors in altitude,
made by every measuring means, using P. F. Zaichikov's
triple control method.

"Malachite" radio theodolites with a range-finding attachment are used by all the aerological stations of the Uzbek Hydrometeorological Service. Observations involving the use of a "Malachite" radio theodolite with range-finding attachments were begun at the Aral Sea and Tamdy stations in April 1964, at the Termez station in September 1964 and at the Tashkent station in July 1965. The radio theodolites at the Aral Sea and Termez stations are stationary, their antenna systems measuring 10.9 and 7.6 meters in height, respectively. The terrain surrounding the radio theodolites at the mentioned points is open. The few obstacles in the path of the radio-wave propagation are due primarily to the negative angle of the horizon cover. Physical secondary reflectors under the 66 to 170° azimuth producing a horizon angle cover up to 0.60 are found only in Termez. The Aral Sea Aerological Station is located at the shore of a bay extending in a southeastern, southern and southwestern direction.

Mobile malachite-type radio theodolites with a 4.2 meter high antenna were installed at the Tandy and Tashkent Aerological Stations. A large number of obstacles in the way of radiowave propagation was noted in Tashkent between 226 and 330°, but in the other directions the horizon cover is insignificant. The slope of the site from the center to the periphery in the area of the predominant balloon directions is 1-2 meters per 100 meters of horizontal distance. The "Malachite" radio theodolite is arranged at the highest point as compared to the adjacent areas. At the Tamdy station the largest number of secondary reflectors are arranged in the main direction of the balloon movement --- from 351 to 125°; some obstacles are encountered also in the

191-230° sector. The other directions, from 126 to 190° and from 231 to 350° are open.

The operating range of vertical angles at the stations under consideration was limited to the following minimum angles: at the Aral Sea station 14.00 in all directions: at the Termez station 14.50 in all directions: at the Tamdy station 14.50 in directions free from secondary reflectors: Tamdy station 16.00 in the sectors with a large horizon cover: Tashkent station 18.00 in the area with a large number of secondary reflectors: Tashkent station 17.00 in the direction of the predominant balloon movement: Tashkent station 16.00 in the other sectors free from secondary reflectors.

The mentioned magnitudes of the minimum vertical angles at all stations have been established without regard to the season.

The altitudes H. and H. compared in this study were calculated by the slant range and the reading of the radiosonde pressure unit for all the mentioned stations. The results of the following observations were used in this comparison: at the Tamdy station for September-October 1964, Tashkent station for August-September 1965, Aral Sea station August-September 1966, and at the Termez station for August-October 1966. A total of 208 ascents from the four stations, each lasting an average of 68 minutes, were used for the mentioned comparison. The plotting of an altitude graph to determine H. 2 and the introduction of altitude corrections for the earth curvature and radio wave refraction were made in accordance with (Ref. 5).

The difference in altitudes alone is not enough to estimate the divergence between H_{R}/C and H_{R}/C . A clearer characteristic of the altitude convergence is provided by the following magnitude $z = \frac{H_{R}/C}{L} \cdot \frac{H_{R}/C}{L} \cdot \frac{100}{L}$. The percent ratio of

the altitude differences AH was calculated from Has

because of the lesser possibility of accidental errors in the calculation of I'A as compared to I'A.

Table 1
The Relation Between the Average /z/ Hagnitudes and the Duration of the Observations

 			سيوسك السباري والمناب وسيور	_
0-10 min.	12-40 min.	40 min.	Average	
6	3	5	4	
6	5	7	5	
13	6	5	7	
16	7	3	8 .	
10	5	5	6 ,	1

The absolute magnitude /z/, as determined by the duration of the observation, is shown in Table 1.

The large number of significant altitude differences seen in the first minutes of observation can be explained not only by errors in measuring the slant range but also by the small magnitude $H_{1/5}$ from which the percentage content of $\triangle H$ was calculated. In the following minutes of observation the /z/ magnitude is reduced on an average to 5 percent. At the Aral Sea and Tamdy stations the smallest /z/ magnitude $(3 \circ 5\%)$ is observed between 12 and 40 minutes, but it is somewhat increased later on $(5 \circ 7\%)$. At Tashkent and especially Termez the average /z/ magnitudes, noted between 12 and 20-30 minutes, amounts to $6 \circ 7\%$, and are then reduced to $5 \circ 3\%$.

The percentage recurrence of various /z/ magnitudes for various vertical angles and slant ranges has been calculated in order to estimate the relationship between /z/ and the changing balloon coordinates. Cited in tables 2 and 3 is the relation between the percentage recurrence of the /z/ gradations (0 = 5, 6 = 10, 11 = 20, 21 = 30, and 31 = 40%) and the vertical angle gradations from 0 to 90° in 5° intervals and a slant range from 0 to 120 kilometers in 10 kilometer intervals,

The total number of comparisons n from which the percentage recurrence of /z/ with various vertical angles and slant ranges was calculated, is cited in the last column of tables 2 and 3.

Table 2. Securence o' varions /r/ redaidons in relation so vertical ande

and the state of t

•	d	1325 476 126 30 4	612 231 156 30	1185 895 585 99 22	912 355 303 134 34
•	85- 90	1111	1111	i e e l l	!
	80- 85	1 1 1 1 1	111	eeei i	14871
!	757 80		I H M I I		1 1 4 7 1
(2)	70-	-111	16411	644 7 1	1 6 7 9 1
(0)0 TO 1 OF 1	65- 70	# 1 2 1 1	павет	1 4 10 4 4	1 8 113 16
	60 -	2 2 1	2 3 10	19044	2 8 10 15 38
81218	55- 60	3 4 2 10 10	64461	4 4 8 14	3 8 11 10 16
TROUGH	50- 55	94661	ወጠቁጠ	7 7 8 7 7	4 8 10 7
ABL	45-	K 4 4 1 1	2 2 100 100	4 7 7 4 6	5 8 10 7 11
	40-	9 5 23	NV 4 W I	04740	911195
	35- 40	12 10 5 7	N 80 4 V I	6 6 6 9 1 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2	7 8 8 6 5
	30-	16 7 9 -	10 8 8 4 1	ထောက္ထာ၊	117 7 7 2 7
	25-	17 11 8 7	12 7 8 10	13.	17 8 9 7 1
	20- 25	14 22 13 - 25	1 8 8 1 1 2 9	14 11 11 8 9	75 75 75 75 75 75 75 75 75 75 75 75 75 7
ا	15-	9 26 23 47	16 16 24 20	11 13 10 36	100 4 1 1
Traintie.	10- 15	2 18 23 50	21 28 30 -	2112116	1150
	%[2]	0-5 6-10 11-20 21-30 31-40	0-5 6-10 11-20 21-30 31-40	0-5 6-10 11-20 21-30 31-40	0-5 6-10 11-20 21-30 31-40
	Station	Aral Son	ुड,जी व ,प्र	Taskent	Ternez

Recurrence of various /z/ radations in relation to a slant range Table 3.

	grada-			•									_	
Station .	tion					lant	range	la	1				•	_
:	[z]	0-	10-	20-	30-	40-	50-	60-	70-	-03	90-	100-	110-	
	7	10	20	30	40	50	60	70	80	90	100	110	120	n
			-							-				
Aral Sea	0-5	39	25	14	9	9	2	1	1	-	-	-	-	1387
WINT DES	6-10	29	5	16	23	13	10	2	1	-	-	-	-	442
	11-20	41	6	3	13	9	9	8	6	1	-	1	1	109
	21-30	40		-	10	5	-	5	-	3	10	5	5	20
~	31-40	67	-	-	-	-	-	-	-	-	33	-	-	3
Tamday	0-5	35	16	11	8	6	4	8	4	3	1	3	1	639
	6-10	35	13	3	5	6	10	11	4	7	3	1	2	211
	11-20	29	4	8	8	4	9	16	8	8	2	1	3	148
	21-30	-39	7	7	3	7	3	10	7	3	7	7	-	29
	31-40	33	-	-	-	-	′	-	-	-	-	33	34	3
			-				_							
Tashkent	0-5	14	22	19	15	14	7	3	3	1	1	1	-	1210
	6-10	33	18	14	11	10	5	5	2	1	1	-	-	890
	11-20	63	14	4	5	- 4	4	3	2	-	-	1	-	563
	21-30	77	12	7	2	1	30-70	1	-	-	-	-	-	101
•	31~40	48	. 28	10	14	. =	-	-	-	-	-	•	-	22
Termaz	۸ -	10					10		2	1		_	_	1087
161. HZ	0-5	10	12	14	17	17	19	8	2	1	_	_		313
	6-10	32	28	7	* 8 * 3	~ -7	7	7	4	-	_	_		
	11-20	65	11	7 2	3	5	1		1	_	_	_	_	225 87
	21-30	82	16	2		_	-			_	_			26
	31-40	100	_			_	_							20

An analysis of the recurrence of various /z/ gradations in relation to the vertical angle reveals the predominance of /z/ < 5 at the stations: for $25 \div 55^{\circ}$ angles at the Aral Sea, $20 \div 35^{\circ}$ and $45 \div 55^{\circ}$ at Tamdy, $35 \div 45^{\circ}$ at Tashkent, and $15 \div 30^{\circ}$ at Termez. There is a noticeable increase in the recurrence of /z/ > 10 for vertical angles larger than 55° at all stations, and less than 20° at the Aral Sea and Tamdy stations and over 45° at the Tashkent and Termez stations.

A comparison of the data obtained at the various stations has established that the greatest recurrence of $/z/\leqslant 5$ is characteristic of $10-25^{\circ}$ angles at the Tamdy and Termez stations, and $25-55^{\circ}$ at the Aral Sea station. The lowest recurrence of $/z/\leqslant 5$ is in Tashkent. The highest recurrence of the $5\leqslant/z/\leqslant 10$ interval with $10-25^{\circ}$ angles is noted at the Tamdy and Aral Sea stations, and with $25-70^{\circ}$ angles at Termez. /z/>10 most frequently occurs at the Aral Sea and Tamdy stations at $10-25^{\circ}$ angles. There is a marked predominance of such differences at angles exceeding 25° at Tashkent and Termez.

Thus the greatest convergence of Har and Har is noted at small vertical angles: 10 - 250 at the Termez station and 25 - 550 at the Aral Sea and Tamby stations. The poorest convergence of the readings along the entire range of vertical angles was noted in Tashkent.

High /z/ values were frequently revealed for D \leq 10 \div 15 slant ranges at the Tamdy and Tashkent stations and for D < 20 + 25 at the Termez station in the beginning of the observation (Table 3). The predominance of the lowest /z/ values is characteristic of Tashkent at 15 < D < 60, Termez at 25 < D < 65, Tadmy at 15 & D & 45 and Aral Sea station at 0 < D < 25. The recurrence of the other /z/ gradations is inversely proportional to their magnitudes at the Aral Sea, Tashkent and Termez stations, and at the Aral Sea station $/z/=6\div10$ is predominant at 25∠ D ≤ 55. In the case of slant ranges larger than those shown above, the recurrence of larger /z/ values increased at the Aral Sea and Tamdy stations, and at Tashkent and Termez the magnitudes of such recurrences were smaller and there were no sharp differences between them. A comparison of the data applying to different stations revealed the highest recurrence of small z for $D \le 20 + 25$ at the Aral Sea and Tamdy stations, and for D > 25 at Termez: /z/> 5 was most frequently noted at D \ 20 + 25 at Tashkent and Termes, and at D > 25 at the Aral sea and Tamdy stations. Consequently, the greatest convergence of Hard and Hard when the balloon moved a short distance away (under 25 kilometer) at the Aral Sea and Tamdy stations, and at D>25 at Termez. In the majority of the D 20 cases in Tash-kent the recurrence of low /z/ magnitudes was less frequent than at all the other stations.

The relation between the magnitude and recurrence of z and the combination of vertical angle and slant range gradations can be traced by the figuresof Table 4. That table shows the z magnitude for five slant range and vertical angle gradatic is.

Slant range gradations: 0 - 10, 10 - 20, 20 - 40, 40 - 70, 70 km; vertical angle gradations: $90 \div 70$, $70 \div 50$, $50 \div 30^\circ$, 30° - minimum angle, minimum angle - 0° .

The number of parallel altitude readings at each station for any gradation of the vertical angle and slant range is cited in Table 4. A reduction in the number of parallel readings is characteristic of the largest and smallest vertical angles and the large (D > 70) slant ranges. The table also includes information on the percentage content of

 $z \le 0$ (H_A) \angle H_A) cases in the total number of parallel altitude readings.

Information on the recurrence & magnitude of /z/ in relation to the vertical angle and slant range

			v 70	,	,	1	9	10	ı	1	j	9	80	ı	1	,	10	7	ı	ı	1	4	9	
4.	/2/		40-70	١	10	4	9;	-	j	,	1	00	9	1	7	<u> </u>	9	5	ı			m		
Table	Average		20-40		00	3	50.0	O ,	ł	1	m	5	7	ı	1	m	5	9	14	9	m	m	4	
	Av		10-20	3	2	3	_ا ب	n	ı	1	5	7	7	ı	5	7	6	14	25	11	9	18	ı	
,			0-10	3	9	9	4	1	6	9	2	3	1	10	11	10	13	48	14	23	11	10	1	
	(in per- number	e (km)	>70	1	i	1	8 5	77	į	ı	l:	9	99	İ	ı	1	100	49	ı	ı	1	40	ı	
	0 (in al num s)	range	40-70	1	0	57	91	<u> </u>	1	1	1	41	58	1	100	83	95	79	ı	100	^	34	71	
	e Of Z O of total of cases)	slant	20-40	1	7	57	86	76	1	1	ı	29	38	ı	ı	89	93	82	ı	16	24	28	100	
	Recurrence Of centage of of centage of centa	one of	10-20	10	30	34	29	o C	ı	ı	25	47	.1	1	100	92	66	100		7	15	30	j	
	Recu	Gradations	0-10	0	18	21	24		17	36	41	77	ı	97	66	96	100	100	-	6	25	23	ı	
		Ö	>70	ı	ı	1	18	3	j	,	ı	01	146	1	1	ı	14	55	·	i	ı	53	, - 1	
	er Of ons		40-70	ı	5	93	172	ì	ı	1	1	87	114		7	77	188	150	ı	. 2	66	459	17	
×	tal Number Of Comparisons	•	20-40	ı	51	143	162	}	ı	1	7	130	37	ı	ı	116	231	79	Ю	20	126	286	-	
	Tota		10-20	29	125	387	221 8) ai	1	1	71	74	7	ı	36	140	125	17	5	54	167	20	ı	
			0-10	4	26	139	787		30	109	166	52	,	20	209	158	77	2	77	152	153	13	ı	
	Vertical Angle Gradations (0)	a.		90-70	70-50	50-30	30-B.y.		02-06	70-50	50-30	30-m.y.	m.y0	90-70	70-50	50-30	30-ш.у.	m.y0	90-70	70-50	50-30	30-m.y.	ш.у0	
	Station			Aral Sea					Tamdy					Tashkent					Termez					

m.y. -- minimum angle

Cases of Hard Linds are predominant in Tashkent. In Termez below the D = 40 in the working range of vertical angles the number of z < 0 cases does not exceed 30% of the total number of readings. With D>40, z < 0 is found in 40% of the cases at this station, and with small vertical angles in 70 = 100% of the cases. At the Aral Sea and Tamdy stations the recurrence of z < 0 cases also increase: ith large slant ranges and small vertical angles. In the other cases, various signs of z are equiprobable.

The average magnitude of /z/ is also shown in Table 4. A rising /z/ value was noted at the beginning of the observation at all stations. The lowest mean values of /z/ were found at the Aral Sea and Tamdy stations with $10 \le 0 \le 40$ for any vertical angle, and at Tashkent and Termez with $20 \le 0 \le 70$, while at Tashkent /z/ increased in the area of small vertical angles, and at Termez in the area of large angles, especially with $b = 70 \div 90^{\circ}$.

The figures shown in Table 4 characterize the altitude divergence in the direction of the predominant balloon movement as the majority of parallel altitude readings apply to this sector of observations. To characterize the relations between /z/ and the conditions of the surrounding terrain, /z/ magnitudes were selected for the areas not included in the sector of the predominant wind direction; at Tashkent and Tamdy it applied to a section free from secondary reflectors, and at the Aral Sea station to sea and land (Table 5).

A comparison of the figures cited in Tables 4 and 5 shows that at the Aral Sea station the average /z/ magnitude above the sea is considerably smaller than above the land. It does not exceed 4-5% of the radiosonde altitude in all the slant range and vertical angle gradations. In the section above the land opposite to the prevailing direction of the winds the figures in Table 5 are similar to those shown in Table 4; they increase only at small vertical angles and $6=50\pm70^{\circ}$ angles at distances over 20 kilometers.

The average /z/ magnitude for an open section in Tamdy is somewhat smaller than in Table 4. An increasing /z/ magnitude was noted only in cases of small (D<10) and large (D>70) slant ranges for vertical angles of 30+16°. In the area with a large number of secondary reflectors similarly located in the opposite direction of the prevailing winds, all the average / magnitudes are larger than the appropriate values shown in Table 4.

The relation between /z/ and available secondary reflectors and characteristics of the radiotheodolite platform-stand

	Tamdy	closed section		10- 20- 40- >70 20 40 70	1	1	1	1	1	
	Tamdy	closed section		20- 40- 40 70			ı	1	ı	-
	Tamdy	closed sec		40		1				
the radiotherdolite platform-stand	Tamdy	closed					1	1	ì	
	Tandy	c10	1	וייבו	1	ı	-	1	!	
	Tamdy			901	16	^	9	4		
and				>70	1	ı	1	1	1	
ונונ		ton		40-	1	1	ı	10	ı	
platform-stand		open section		20- 40	1	ı	7	n	ı	-
atfo		pen		10- 20	ı	1	8	1	ı	
e pl		0	(Eg	901	6	4	4	v	1	
the radiotheodolite			ns (> 70	-	1	ı	ı	, 1	
heod	t	ton	atio	40-	i	4	4	7	14	
diot	Tashkent	open section	gradations	10- 20- 40- >70 20 40 70	ı	1	4	9	∞	
e ra	Tas	pen	range	10- 20	Ī	. v	4	œ	13	
		0		0- 10	J	==	12	14	22	
C SO			slant	>70	. 1	1	ı	• •	43	
isti				20- 40- 40 70	- 1	22	4	•	17	
characteristics of t		Land		20- 40	1	11	2	5	6	
chara		1		10 - 20	3	r +	2	4	7	
ט די	Aral Sea			0- 10	2	4	^	4	1	
-	Aral			>70	_	1	ı	ı	I	
				20- 40- 40 70	ı	ı	4	ı	ı	
		sea		20- 40	0	m	4	\$	2	
				10- 20	E	7	rr.	6	4	
	İ	3		0- 10	3	m	4	7	1	
		-1	818	Verti angle datio	90-70	70-50	50-30	30-m.y.	m.y0	

There is no marked difference between the figures of Table 4 and 5 for Tashkent. This obviously depends on the similarity of the conditions in the prevailing directions of the wind and the free additional sector. With small angles at D>10, the figures in Table 4 are larger than the analogical values in Table 5. The average /s/ magnitudes for the sector in Tashkent with a large horizon cover are not given because of the insignificant number of comparative readings.

It appears from the results of the above-shown altitude comparisons that in the majority of cases the figures for the Aral Sea and Tamdy stations (with sandy soil), and Tashkent and Termez (with clay soil) are similar in pairs. The altitude divergence apparently depends to a large extent on the characteristic features of the subjacent media and their electrical properties (for example, electric conductivity) as compared to to the effect of secondary reflectors and the height of the antenna above the ground surface. We know from the theory of radio-wave propagation in stratified media (1) that the field strength of the areas with a good electric conductivity (the sea and clay soil) is higher than the media with a poor conductivity (land, sandy soil, limestones). There is a better convergence of the Half and Has altitudes above the media characterized by a higher field strength, especially at the end of the observation when the power of the incoming signal grows weaker because of the great distance from the balloon.

The specialist engaged in the numerical methods of fore-casting might be interested in the accuracy of determining the altitude of the major isobaric surfaces. The altitude of the isobaric surfaces was calculated on the basis of the radar measured altitude in accordance with (10) for the purpose of comparing the altitudes at the mentioned levels. A comparison of the Ha/4 and Ha/5 altitudes on the isobaric levels shows that at the Aral Sea, Tamby and Termez stations /z/ does not exceed 1 = 2% beyond 700 = 600 millibars, and at Tashkent it does not exceed 3% beyond 600 millibars and 2% beyond 300 = 400 millibars.

A comparison of the signs of the difference revealed a predominance of Ha/s over Ha/s at the Aral Sea and Tashkent stations in 100% of the cases, at Tamby in 90% and at Termez in 79% of the cases.

It would thus be wrong to extend the divergence of the Haff and Haff altitudes during the specific readings to the altitude difference of the main isobaric surfaces found by the two mentioned processing methods. The divergencies between the altitudes of the main isobaric surfaces are less than at ceratain moments of time because of the averaging-out method used in the processing.

To calculate the errors permissible in the determination of the Hard and Hard altitudes, the latter x re compared to the Hard stitudes found by the simultaneous base-line pilot balleen observations at the Aral Sea, Tashkent and Termez stations.

A PROPERTY OF THE PROPERTY OF

The base-line observations were made and processed according to the requirements in (8). The length of the base line at the Aral Sea station was 1050 meters, at Tushkent 490 and 3250 meters, and at Termez 430 meters.

A total of 27 base-line observations of the radiosondes and 10 observations of the radio pilots, each lasting an average of 21-22 minutes, were carried out at the three stations. The total number of parallel readings resulting from the radiosonde observations was 336, and radio pilot observations 143. The simultaneous measurements of Ham and Ham were taken from the situate-time ratio graphs. The Hi altitude defined by the analytical method was not averaged out but included in the treatment in the form it had been found during the calculations made for certain minutes of observations. Consequently, it was not the averaged value of the Hi altitude that was used for comparison purposes but the actual value reflecting the vertical currents which are considerable in the atmospheric layer under consideration.

The following differences were calculated for every three parallel readings of the altitude:

Ho - Hop. Ho - Hop. Hos - Hos.

where H₅ is the altitude calculated by the results of the base-line pilot balloon observations. An analysis of the signs of the resulting differences reveals that H₅ < H_A in 85 = 89% of the cases at all stations. H₅ < H_A at the Aral Sea station in most cases throughout the observation (an average of 80%). A different picture was observable at the Tashkent and Termez stations: H₅> H_A in about 53 = 61% of the cases. H_A < H_A at the Aral Sea, Tashkent and Termez stations in 69, 88 and 95% of the cases, respectively.

In the case of the base-line observations of the transponder, $H_{\alpha/\delta}$ exceeded H_{δ} in most of the cases (85%), a reverse altitude correlation was noted in 14% of the cases, and $H_{\alpha/\delta} = H_{\delta}$ in 1% of the cases.

The triple control method proposed by P. F. Zaichikov (2, 3) was used for calculating the systematic and random errors in the determination of the altitude by various methods.

Every minute of observation was processed by the triple control method. Hagnitudes of the simultaneous altitude measurements were selected by the mentioned three methods for each of the three stations as well as for all the stations together (Table 6). The observation data for the Tormez station are conditional because of the small number of cases.

The systematic error in each measuring method was determined on the basis of the recommendations in (3) by the use of arithmetic mean differences. Assuming that the systematic error of one of the measuring methods equals zero, it is possible to find the systematic errors of the other two AH methods. In the case under consideration it would be more natural to assume the absence of a systematic error in the base-line without of altitude measurement. To determine the systematic error in measuring Haff and Haff, such an error in base-line observations was assumed to be the nonexistent AHg = 0.

The random error for each method of measurement was calculated according to (3) by the following formula

where N is the number of methods of simultaneous measurements, it the dispersion magnitude (the square of the average quaderatic error) of each of the N methods of simultaneous measurements, it is mean quadratic difference of the simultaneous altitude measurements by two methods.

The reliability of the determination of errors, depending on the accuracy of calculating the mean quadratic error (2, 3), was calculated in addition to the systematic Δ II and the mean quadratic with σ of errors,

$$AAH_{i} = \sqrt{\frac{1}{(N-2)(n-1)}\sum_{j=1}^{N} z_{i-j}^{2}}$$

The average \triangle H, the mean quadratic errors in determining the altitude, and the reliability of determining the \triangle II errors by the three measuring methods are cited in Table 6. The systematic error in defining $\Pi_{A/S}$ at all stations is markedly greater than the similar error in measuring $\Pi_{A/S}$. In the case of $\Pi_{A/S}$ and $\Pi_{A/S}$ the systematic error increases with time, while the increase of \triangle II, begins in the first minutes of observation, and \triangle Ha/S reveals a marked increase after 10 minutes. The systematic \triangle Ha/S errors were negative throughout the observations, and approximately similar in magnitude at all the three stations. \triangle Ha/S is preceded primarily by a positive sign in Tashkent and Termez, and by a negative sign at the Aral Sea station.

Mean and mean quadratic errors (m) in determining the altitude measurements (r/l) according to the base-line pilot balloon, radio sounding (r/s) and radar data

Table 6.

Station	Method								min.	angle
	of Measuzement		1		-	2			· 3	
	Min.	ΔH	σ	AAH	ΔΗ	σ	DAH	ΔΗ	σ	ΔΔΗ.
Aral Šea	6 a 3	. 0	67	±57	0	26	±29	0	64	±48
	p/3 p/n	-12 -7	17 20	±41 ±45	-44 -23	51 30	±34 ±29	-71 -48	49 76	±45 ±50
Tashkent	6аз	0	22	±19	0	33	±28 ±29	0 -62	0 56	±33 ±38
.* . • • • • • • • • • • • • • • • • • • •	p/3 p//:	-25 -11	0 41	±16 ±22	-22 0	- 39 54	133	- 8	100	±45
Termez	6 a 3	0	0	±95	-0-	78	±94	0	87	±119
	p/3 p/ <i>a</i> ;	65 12	10J 142	±114 ±128	-30 90	96	±62 ±102	-77 11	140	±80 ±142
General	6a3	0	51	±29	0	39	±22	0	48	±28
	p/3 p/s;	-4	52 67	±29 ±31	-32 6	36 70	±22 ±26	-67 -7	35 104	±26 ±33

Station	Measuring								·	
	Method		9			10			12	
		ΔΗ	σ	ΔΔ Η	ΔΗ	σ	ΔΔ Η	ΔH	σ	ΔΔΗ
Aral Sea	6a ₃	0	110	±62	0	84	±60	0	60	±75
	p/3	-197	0	±44	-215	54	±53	-203	94	±81
	p/n	-121	58	±50	-102	44	±51	-98	108	±85
Tashkent	6a3	0	126	±95	0	184	±82	0	1821	±105
	p/3	-1 74	0	±81	-1 9 0	169	±79	-187	82	±68
	p/√	52	214	±113	23	238	±95	81	126	±94
Termez	6a3	0	87	±96	0	58	±87	0	147	±168
	p/3	-170	0	±67	-247	66	±86	-220	121	±158
	p/a	60	74	±91	-30	122	±79	63	0	±131
General	6аз	0	121	±52	0	109	±51	0	132	±60
	p/з	-183	0	±42	-206	64	±48	-198	92	±56
	p/л	-16	168	±59	-22	154	±57	18	135	±61

Table 6 -- continued

Tb1														
	4			5			6			7			8	
۲μ	σ	4 24	ΔH	σ	DAH	ΔН	σ	ΔΔΗ	Δ/-/	D	$\Delta \Delta H$	ΔH	σ	ΔΔH
0 -70 -53 0 -84	73 0 61 142 70	±42 ±35 ±40 ±71 ±60	0 -127	94 0 93 60 109	±35 ±28 ±35 ±31 ±31	-121 -86 0 -111	0 100	±88 ±46 ±84 ±62 ±71	0 -104 -56 0 -152	52 17 49 65 76	±36 ±30 ±35 ±59 ±60	0 -126 -48 0 -143	68 10 52 22 77	±42 ±33 ±39 ±68 ±73
25 0 -103 100 6 -81 6	120 74 10 108 116 44 113	±67 ±107 ±93 ±119 ±42 ±35 ±42	0 -120	124 0 66 88 57 91 125	±36 ±33 ±47 ±53 ±21 ±39 ±43	0 ~160 57 0 ~116	0 21 100 0	±88 ±68 ±89 ±104 ±42 ±40 ±55	43 0 -190 40 0 -142 11	157 0 52 87 47 73 135	±73 ±61 ±76 ±91 ±36 ±39 ±45	72 0 -177 37 0 -142 19	176 66 0 101 53 50 0	±92 ±89 ±68 ±105 ±20 ±20 ±14

Tb1											
	14			16			18			20	
ΔΗ	σ	ΔΔΗ	ΔH	σ	ΔΔΗ	ΔΗ	σ	ΔΔΗΗ	ΔH	σ	$\Delta \Delta H$
0 -333 -193	80 20 158 254	±87 ±80 ±106 ±131	0 -292 -212 0	- - 172	- - - ±92	0 -172 110 0	- - 105	- ±81	0 -297 -160 0		1 1 1 1
-144 154 0 -190	98 179 40 155	±108 ±118 - -	-322 35 0 -205	48 181 - -	±78 ±94 - -	-194 113 - -	77 110 - -	±76 ±82 - -	-215 130 - -		- ' - -
170 0 -220 98	0 236 97 192	±93 ±79 ±88	160 0 302 -1	161 165 100	±72 ±73 ±66	0 -218 94	150 72 111	±75 ±64 ±68	- 0 -250 6	271 0 186	±170 ±125 ±150

In view of the above, it may be concluded that the radar method of altitude determination produces a smaller systematic error than H_D/5. The considerable magnitudes of the random errors in determining H_D/5 are due to the method of radio-wind observations whereby the accuracy of the readings of the slant range and the angle coordinates depends in large measure on subjective factors: the simultaneousness of the readings, the experience of the observer and the extent of his concentration.

In conclusion, a simultaneous processing of two radiowind observations of the radiosonde was carried out by three methods:

- 1) the processing of $\Lambda=30=D$ on a drawing table based on the slant range and the interpolation for standard altitudes of wind velocity and direction for the $H_{a/5}$ altitude:
- 2) the processing of A = 30 = D on a drawing board based on the slant range and interpolation for the H_{A}/C altitude:
- 3) the processing based on a conditional vertical speed and interpolation for the IL/6 altitude.

The following differences were calculated in the comparison of the three above-indicated processing methods:

$$\Delta V_1 = V_1 - V_2$$
 $\Delta d_1 = d_1 - d_2$
 $\Delta V_2 = V_1 - V_3$ $\Delta d_2 = d_1 - d_3$
 $\Delta V_3 = V_2 - V_3$ $\Delta d_1 = d_2 - d_3$

where V_1 and d_1 are the speed and direction of the wind defined by the first processing method, and V_2 and d_2 , V_3 and d_3 are the same magnitude found by the second and third methods respectively.

The average divergencies of the wind velocity between the data computed by various methods are small for all the altitudes, and do not exceed 2 m/sec. for ΔV_1 , ΔV_2 and ΔV_3 . The maximum differences are: $\Delta V_{1\text{max}} = 5 \text{ m/sec}$, $\Delta V_{2\text{max}} = 3+5 \text{ m/sec}$. and $\Delta V_{3\text{max}} = 4+6 \text{ m/sec}$.

The divergencies between the wind directions computed by the first and second, second and third methods are of considerable magnitude: $\Delta d_1 = 37 + 62^\circ$: $\Delta d_2 = 40 + 62^\circ$. These divergencies are not large for the direction values determined by the first and third methods where the interpolation is fulfilled for 14/4, $\Delta d_2 = 6 + 7^\circ$.

The changes of the maximum differences in the wind direction $\Delta d_{1_{max}} = 98 \div 205^{\circ}$, $\Delta d_{2_{max}} = 23 \div 38^{\circ}$, $\Delta d_{3_{max}} = 90 \div 188^{\circ}$ are similar to those of the average differences.

Thus the large II and II and II altitude divergencies account for the considerable Ad magnitudes, and in this connection it is recommended that the interpolation of the windage for standard altitudes during the processing of the wind data be carried out between the altitudes of the middle parts of the layers determined by II .

Conclusions

- 1. A comparison of the Ha/l and Ha/s altitudes reveals that Ha/l Ha/s in most cases in Tashkent, and Ha/l Ha/s in Termez: at the Aral Sea and Tamby stations different signs of the altitude differences are equiprobable.
- 2. At the Aral Sea and Tamdy stations the /z/ magnitude did not exceed 5% in the middle of the observation (under 40 minutes), and increased to 5 7% by the end of it. In Tashkent and Termez /z/ amounted to 6 7% for 20 30 minutes, and then dropped to 5 3%.
- 3. The difference between the H_{n}/s and H_{a}/ℓ altitudes depends on the balloon coordinates (5, D), and increases in the direction of the smallest and largest vertical angles and large slant ranges.
- 4. The altitude convergence above the sea is better than above land, which is explained by the greater field strength above a water surface.

- 5. The divergence between the Hope and Hope altitudes depends on the characteristic features of the subjacent media and their electrical properties. Similar data on the changing altitudes were noted at the Aral Sea and Tamby stations (with sandy soil) and Tashkent and Termez (with clay soil).
- 6. The altitude divergence is greater in the observation sectors with a large number of secondary reflectors.
- 7. The systematic space IIn/s error always exceeds AIIn/s. The sign of AIIn/s is always negative. In Tashkent and Termez the sign of AIIn/s is mostly positive, and at the Aral Sea station negative.
- 8. The mean quadratic errors made in the altitude measurements are smallest for $\mathbb{R}_{n/s}$ and largest for $\mathbb{R}_{n/s}$.
- 9. At fixed moments of observation the reliability of determining the errors at all stations is approximately the same for the various observation methods.
- 10. The tendency of every type of error is to increase with time.
- II. When processing the windage data for a slant range it is advisable to interpolate the wind only between the Lage altitudes.

Bibliography

- 1. Brekhovskikh, D. M. Waves in Stratified Hedia. USSR Academy of Sciences, Moscow, 1957.
- 2. Zaichikov, P. F. Preliminary Processing Results of the Observation Materials of the Second International Radiosonde Comparison. Transactions of TsAO (Central Aerological Observatory), No. 22, 1957.
- 3. Zaichikov, P. F. Some Additions to the "Triple Control" Hethod. The Accuracy of Independent Methods of Determining the Altitude of a Hoisted System. Transactions of TsAO, No. 50,1964.
- 4. Harfenko, O. V. Substantiating the Hethods of Processing Wind Observations by the Use of a "Halachite" Radio Theodolite with a Range-Finding Attachment. Transactions of TsAO, No. 60, 1964.

- 5. TsAO's Methodical Instructions, No. 29. Gidrometeo-izdat Publishing Mouse, Moscow, 1963.
- 6. Instructions for Hydrometeorological Stations and Outposts, Part III, No. 4. Gidrometeoizdat Publishing House, Leningrad, 1966.
- 7. Instructions for Hydrometeorological Stations and Outposts, Part VI, No. 4. Radio-wind Observations. Gidrometeo-izdat, Moscow, 1960.
- 3. Instructions for Hydrometeorological Stations and Outposts, Part II, No. 4. Pilot Balloon Observations (Base Line), Gidrometeoizdat, Leningrad-Moscow, 1945.
- 9. Reshetov, V. D. Measuring the Range of Radio Pilots. TsAO Transactions, No. 16, 1956.
- 10. Instruction on Probing the Atmosphere with an RKZ-lA Radiosonde. TrAO. Gidrometeoizdat, Moscow.

UNCLASSIFIED			
Exercity Classification			
SOCOLERY CONT			
(Security classification of title, hody of should and indexing	arripletion must be es		
1. SRIGHATING ACTIVITY (Conscion suffer)	-	is. REPORT DE	SURITY CLASSIFICATION
Foreign Science and Technology Center			UNCLASSIFIED
US Army Materiel Command		M. GROUP	
Department of the Army			
3. HEPORT TITLE			
ACCURACY IN DETERMINING THE HIGHT OF A RA			
ATTACHMENT TO MALAKHIT RADIOTHEODOLITE AT		STATION	OF THE
HYDROMETEOROGICAL SERVICE OF THE UZBEK SS	SR.		
4. DESCRIPTIVE NOTES (Type of separt and inclusive dates)	•		
Translation			
5- AUTHOR(8) (First name, middle initial, last name)			
S. A. BUDARINA			
	in the second		
6. REPORT DATE	74. TOTAL NO. OF	PAGES	75. HO. OF REFE
June 3 1970	18		N/A
SE CONTRACT OR GRANT NO.	SO. ORIGINATOR'S	REPORT HUMF	HE (18)
	i		
A. PHOJECT NO.			-
	FSTC-HT-2	3- 255-70	
◆02RD500 2301	SHE COOK!	T HOLD (Amy of	her rembers that may be assigned
USAECOM (WSMR)	ACSI Cont	rol Number	J-//13
16. DISTRIBUTION STATEMENT			
This document has been approved for publ	ic release a	nd sale;	its distribution
is unlimited.	I The top of the second	*	
11- SUPPLEMENTARY NOTES	12. SPONSORING M	LITARY ACTIV	VIYY
	US Army Fo	reign Sci	ence and Technology
. + 66	Center		
		•	
IB. ASSTRACT			
Cited in this article are the resul	to often alt	tendo com	martan based
			-
on a reading of a radiosonde pressure un			
slant range with a range-finding, attach			
The relationship between the altitude di			
the sheltered location of the horizontal			
subjacent media has been established. I	The results o	f special	base-line
observations were used to calculated the	systematic	and mean	square errors in
altitude, made by every measuring means,	using P. F.	Zaichiko	v's triple control
method.	~		

UNCLASSIFIED
Security Classification

INCLASSIFIED

Sycurity Classifiesities							<u> </u>
REV WORDS		Link		LIM		L 864	
		not 8	**	MOFE	WT	MOFE	97
Radiosonde pressure unit							
Radiosonde pressure unit "Malachite" radio theodolte							
Altitude divergence							
P. F. Zaichikov's triple control method							
	-						
		ĺ (•				
•							
•							
•							
			•				
							-
			i				
					!	·	
4							
		-					
		Ì				i i	
l							

UNCL	SSIFIED	
Security	Cio-sification	•